



Virtual Development and Physical Testing Powering InfiMotion's 12-in-1 Electric Drive Unit

Shino George, Dr. Håkan Sandquist, Dr. Simon Klacar

InfiMotion Technology Europe AB

Gothenburg, Sweden

Outline

PART ONE

Who are we?

PART TWO

Our Product Development Philosophy

PART THREE

12 in 1 EDU – Challenge, Solution & Enablers

PART FOUR

Summary

Example of what we have achieved in Europe

– so far

- Supplier of sub-systems to **JLR**
- EDU system supplier for **Lotus Eletre**
- EDU system supplier for purpose-built **German OEM** with FCA Europe
- Software supplier to large **German OEM**
- EDU system supplier to **premium BEV OEM**
- Software supplier to **European premium brand**



Outline

PART ONE

Who are we?

PART TWO

Our Product Development Philosophy

PART THREE


12 in 1 EDU – Challenge, Solution & Enablers

PART FOUR

Summary


PS to SOP in 24 Months


- ◇ InfiMotion's target is PS to SOP in 24 months
- ◇ Simulation Centric Design is key → Frontloading
- ◇ Frontloading of: Requirements Evaluation, Verification and Validation



Challenges in 24 Months to SOP


- **High quality virtual A-sample**
Strong CAE methodologies, design commonality and model correlation
- **Reduced, targeted, “sufficient” testing**
Customer centric DVP, in-house testing, test to failure, in-house prototyping
- **Requirements handling process**
System Engineering, integration of PLM, ALM and requirements handling





Optimizing the relationship increases efficiency and accelerates product development

Virtual EDU Development – Validation & Testing



Eliminating silos between different areas increases productivity

● **Test to correlate**

● **Correlate to extrapolate**

● **Extrapolate to design**

» **High Testing and Virtual capabilities needed**

Testing and verification capabilities

- The first use case of a **30 000 RPM motor test bench in the world**
- Test bench parameters **covering testing requirements of electric drive systems** of passenger cars, light duty, and performance vehicles, covering up to 550kW motor testing
- Compatible with **several voltage platforms** (400V/800V/1000V)
- **Full environmental test capabilities** (altitude, humidity, thermal, vibrations, dust)
- Load **EMC test capabilities**, compatible with EDU, motors, battery packs, static and dynamic EMC test requirements




2 Powertrain tests



10 Environment tests




3 Motor tests



EMC test with load


1

SYSTEM




2

ELECTRICAL




3

ELECTROMAGNETICS




4

STRUCTURE




5

DYNAMICS




6

NVH




7

FLUIDS




8

THERMAL



9

EFFICIENCY



- » 0D/1D/3D Full virtual development capabilities
- » Model factory w. continuous improvement

- » In-house computational resources
- » MIL/SIL/HIL Virtual testing capabilities

Outline

PART ONE

Who are we?

PART TWO

Our Product Development Philosophy


PART THREE

12 in 1 EDU – Challenge, Solution & Enablers


PART FOUR

Summary


Challenge – Vehicle Integration



- Integration of **hardware** functions into the EDU, like PDU, OBC and DCDC leads to reduction of housings, cables, and connectors, as well as simplifying the thermal management system
- Integration of **software** functions into the MCU leads to more efficient use of the controllers
- Compared to previous setup there are **significant benefits**:
 - total space savings of about 5 liters, saving 8%
 - total weight reduction about 3kg, saving 13%,
 - total cost reduction about 20%




Solution – Integration into EDU



Example L402 - Integration into EDU

L402 (12-in-1) function list


- E-machine PMSM, 160 kW
- Reducer Layshaft, Single gear, 2-step
- MCU Motor Control Unit, IGBT 400V
- OBC On board 3-phase AC-charger, 11kW
Bi-directional V2G/V2L-ready
- DC/DC 12V output, 2.5 kW
- PDU Power Distribution Unit
- BMS LV Battery Management System - low voltage
- BMS HV Battery Management System - high voltage
- VCU Vehicle Control Unit
- TMS Thermal Management System
- GWRC Vehicle Stability Control System
- EVCC EV Communication Controller (HVDC Charging)





We just started production of L402 in China for a Chinese OEM

Technology enablers for X in 1 Integration:

- Instead of multi-ECU vehicle system, **integrate applications into the MCU** and delete redundant ECUs
- **Inhouse** development of **hardware** and **software**
 - Enabler to **integrate black box** hardware and software
- The size of **core application** to control the EDU normally range **< 25% of the MCU capacity**
 - **Application load and timing** are important variables to consider when integrating Xin1
- Continuous Integration **Software Factory** enabling fast integration of software components, white or black box



- Application load and timing need to be considered when integrating Xin1 to choose the right controller setup
- CPU architecture and advancements enabler for integration
- Project-specific adaptations multi-role vs. dedicated designs (see L40X and P50X)



Software

Software modularity and re-useability

- E-machine control with various modulation types and control principles
- Adapting single and dual e-machine(s), Park-lock, Disconnect, Oil pump and Wet or Dog-clutch based transmissions

Toolchain

Complete toolchain

- In-house ASW & BSW development and integration
- Software factory with integrated SIL and HIL SW Build and verification (Cloud based)
- Validation and Calibration

Development compliance

Fully compliant

- AUTOSAR,
- OBD OEM diagnostic,
- ISO26262 safety process,
- ASPICE L3 and
- Cyber security

Capabilities

ASW & BSW development


Calibration verification

Application integration

CI of cloud-based software factories

MIL , SIL, HIL and bench test

The V-model as seen from a tooling perspective



Outline

PART ONE

Who are we?

PART TWO

Our Product Development Philosophy


PART THREE

12 in 1 EDU – Challenge, Solution & Enablers

PART FOUR

Summary

- **InfiMotion's Product Development Philosophy**
 - PS to SOP in 24 months
 - Leveraging Virtual Development is key to front-loading and shortening lead times
 - Test to Correlate is a vital step
- **3 Enablers for Frontloading and Virtual EDU Development**
 - People
 - Technology
 - Processes
- **InfiMotion's 12 in 1 EDU → Solution to Challenging Electric Vehicle Systems Integration Issue**
 - Total space savings of about 5 liters, saving 8%
 - Total weight reduction about 3kg, saving 13%,
 - Total cost reduction about 20%



Vielen Dank!

Thank you for your Attention